



HAL-C Series 進給軸用聯軸器 COUPLING FOR FEED SHAFT

特性

- 高扭力・高剛性。
- 高正逆轉特性。
- 低慣性・無背隙。
- 適用於伺服馬達或精密定位傳動。
- 免保養・壽命長。
- 固定方式：夾緊式。
- 本體為鋁合金材質。
- 使用溫度範圍-30°C~100°C。
- High torque, high rigidity.
- High clockwise and anticlockwise rotational characteristics.
- Low inertia, backlash-free.
- Applicable for servo motor or precise positioning transmission.
- Maintenance-free; infinite life.
- Fix type: Clamping.
- Body: Aluminum alloy; light-weight.
- Working range: -30~C~100°C temperature.



產品規格 SPECIFICATIONS

產品型號	A	L	L1	M	S	B	H	D1 x D2		鎖緊扭矩
								Min.	Max.	N.m
HAL-30C	30	35	11	13	1	5	M4	6	16	6
HAL-40C	40	66	25	16	1	8	M5	8	20	7
HAL-55C	55	78	30	18	1.5	10	M6	10	25	12
HAL-65C	65	90	35	20	2	13	M8	12	35	27
HAL-80C	80	114	45	24	2	14	M8-2	15	45	27
HAL-95C	95	126	50	26	3	16	M10	20	55	50

產品型號	常用扭力	最大扭力	容許誤差			最高轉速	剛性靜扭力值		慣性矩	重量
			偏心	偏角	軸向位移					
	N.m	N.m	mm	°	mm	rpm	N.m/	rad	kg.m ²	g
HAL-30C	12.5	25	0.1	1°	1	8,000	135		6.2 x 10 ⁻⁶	40
HAL-40C	17	34	0.1	1°	1.2	8,000	1,100		3.9 x 10 ⁻⁵	150
HAL-55C	60	120	0.1	1°	1.4	7,000	3,200		1.6 x 10 ⁻⁴	350
HAL-65C	160	320	0.1	1°	1.5	5,900	4,900		3.8 x 10 ⁻⁴	500
HAL-80C	325	650	0.1	1°	1.8	4,800	7,400		1.1 x 10 ⁻³	1,000
HAL-95C	450	900	0.1	1°	2	3,600	14,000		1.9 x 10 ⁻³	1,500



HUI-JING ELECTRON CO.,LTD

TEL:+ 886-4-26999859 FAX:+886-4-26997006 <http://www.hui-jing.com.tw>

peter@huijing.com.tw