

HERG Series



FEATURES

Power Supply System DC 5V / DC12V / DC 24V

Line driver output available, besides open collector output.

25 PPR or 100 PPR Available

Provide dimension Ø60 and Ø80 handle wheel to choose

Multiple output type suit for many CNC controllers

Dust and water proof short body and light weight design

Protect inversion of polarity



Series	Model	type	DCPower	PULSE	Singal Mode	Diameter		
HERG	T	A	5V	100PPR	A.B	60	Ø60mm	
	F	B	5V	25PPR	A.B	80	Ø80mm	
	B	C		12V	100PPR	A.B		
		D		12V	25PPR	A.B		
		E	5V Line Drive	100PPR	A.B.A/B/			
		F	5V Line Drive	25PPR	A.B.A/B/			
		G	24V	100PPR	A.B			
		H	24V	25PPR	A.B			
		I	8~26V Line Drive	100PPR	A.B.A/B/			
		J	8~26V Line Drive	25PPR	A.B.A/B/			

	PUSH-PULL	Voltage	Line Driver
SUPPLY VOLTAGE DQ(V)	15±0.25~24v	5~15V	5+0.25 8~26V
CURRENT CONSUMPTION (mA)	≤ 70	≤ 60	≤120
MAX OUTPUT FREQU ENCY (kHz)	0~5	0~5	0~5
RISE TIME	≤ 1	≤ 1	≤ 1
FALL TIME	≤ 1	≤ 1	≤ 1
SINGLE LEVEL HIGH (VH)	≥ Vcc0.7	≥ Vcc-1	≥ 2.5
SINGLE LEVEL LOW (VH)	≥ 1	≤ 0.5	≤ 0.5

